

KOHLER®

SDMO®



DIESEL 15 LC TA SILENCE AVR C5

PORTABLE POWER

GENERATING SET Range DIESEL SILENCE

PRODUCT ADVANTAGES

- Generating set guaranteed 3 years
- KOHLER water-cooled industrial engine
- Very Silent
- Soundproofing and against shocks panels
- Hydrocarbons bulk tank

GENERATOR SMART CARE is a Bluetooth box which can be used on all the brand's portable generators. TECHNOLOGY EQUIPPED WITH AN INNOVATIVE APPLICATION Generator Smart Care is a digital solution which provides access to:- The list of generators- The maintenance due dates- A maintenance aid- The map of reseller partners
The APM202 control panel displays overspeed, starting failure, oil pressure, battery and temperature

Range DIESEL SILENCE

Both long run times and very long life for professional applications.



This product meets the Qualigen charter, which aims to ensure a high level of quality and guarantee the safety of users. Qualigen

DIESEL 15 LC TA SILENCE AVR C5

GENERAL SPECIFICATIONS

| | |
|--|----------------|
| Range | DIESEL SILENCE |
| Frequency (Hz) | 50 Hz |
| Max power (kW) * | 9.50 |
| Max power (kVA) | 11.90 |
| Nominal voltage (V) | 400 |
| Number of Phase | Three phase |
| Fuel | Diesel Fuel |
| Tank (L) | 27 |
| 75% cons. (l/h) * | 2.60 |
| 75% Autonomy (h) * | 10.40 |
| Sound power level guaranteed LwA dB(A) | 94 |
| Acoustic pressure level @1m in dB(A) | 78 |
| Acoustic pressure level @7m in dB(A) | 65 |

ENGINE SPECIFICATIONS

| | |
|---|---------------|
| Engine brand | KOHLER |
| Engine ref. | KDW702 |
| Engine Type | Diesel O.H.V. |
| Start | Electrical |
| Oil shutdown | OUI |
| Displacement (cm3) | 690 |
| Oil system capacity including filters (l) | 1.60 |

ALTERNATOR SPECIFICATIONS

| | |
|--------------------------|------------------|
| Technology | Collar and brush |
| AVR Regulation | Yes |
| Indication of protection | IP 23 |
| Insulation class | H |

PLUGS AND PANEL DESCRIPTIVE

1 230V 10/16A socket - circuit breaker + 3 230V 16A sockets - circuit breaker + 1 400V 16A socket - circuit breaker + emergency stop button + hour meter + indicator + APM202

DIMENSIONS AND WEIGHT

| | |
|-----------------|--------|
| Length (cm) | 121.10 |
| Width (cm) | 79 |
| Height (cm) | 105.60 |
| Dry Weight (kg) | 315 |

PACKAGING

| | |
|------------------------------------|--------|
| Packaging type | Box |
| Length (cm) | 122.20 |
| Width (cm) | 80.40 |
| Height (cm) | 105.60 |
| Weight (kg) | 321 |
| Pallet type | |
| Number of box by pallet | 0 |
| Pallet height (cm) | 0 |
| weight of the packaged Pallet (kg) | 0 |

KOHLER® SDMO®

7/18/2023

DIESEL 15 LC TA SILENCE AVR C5 - PORTABLE POWER - GENERATING SET DIESEL SILENCE

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 - France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com

commitment to safety and quality.



7/18/2023

DIESEL 15 LC TA SILENCE AVR C5 - PORTABLE POWER - GENERATING SET DIESEL SILENCE

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 – France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com

ACCESSORIES SUPPLIED



User and maintenance manual

Battery without maintenance



Lifting eye

Hour meter

OPTIONS



This set includes a differential switch, a hour meter, the plugs and a thermal circuit breaker This set includes a differential switch, a hour meter, the plugs and a thermal circuit breaker.



RSTART2 - Remote control in order to start or stop the generating set until a distance of 50 meters (needs the APM202 control panel) Remote control in order to start or stop the generating set until a distance of 50 meters (needs the APM202 control panel)



VERS050 - Switches over automatically if the mains fails, 40A or 100A 1P or if the mains fails, 25A or 40A 3P (needs the installation of a APM202 control panel). Includes the battery charger Switches over automatically if the mains fails, 40A or 100A 1P or if the mains fails, 25A or 40A 3P (needs the installation of a APM202 control panel). Includes the battery charger.



RKDS6 - Maintenance kit for KOHLER KDW702 Maintenance kit for KOHLER KDW702



RAP - industrial adapter for connecting a 230V device to an industrial socket The adaptor for industrial sockets is used to connect 230-V appliances to the industrial socket.



Male plugs for all models made up of : 2 x 16 A/230 V, EEC17: 1 x 16A/230 V, 1 x 32A/230 V and 1 x 16A/400V Male plugs for all models made up of : 2 x 16 A/230 V, EEC17: 1 x 16A/230 V, 1 x 32A/230 V and 1 x 16A/400V